


* Optional



- › 4 way air discharge and air swing
- › Compact design
- › Built-in high head drain pump
- › Mount with B(Y)C20CXW decorative panel
- › Stylish and slim panel
- › Auto mode
- › Hot keep cycle
- › Self diagnosis
- › Wireless handset BRC52A61 (H/P) or BRC52A62 (C/O) is supplied as standard

Indoor Model Name			FFRN25CXV1	FFRN35CXV1	FFRN50CXV1
Outdoor Model Name			RN25CXV1	RN35CXV1	RN50CXV1
Nominal Cooling Capacity		Btu/h	9500	12500	17500
		W	2780	3660	5129
Nominal EER		W/W	3.09	2.82	3.03
Indoor	Power Supply	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50
	Air Flow	CFM	410/360/330	410/360/330	450/410/340
	Sound Pressure Level	dBA	41/38/35	41/38/34	44/41/37
	Height [with Panel]	mm	250 [295]	250 [295]	250 [295]
	Width [with Panel]	mm	570 [640]	570 [640]	570 [640]
	Depth [with Panel]	mm	570 [640]	570 [640]	570 [640]
	Net Weight [with Panel]	kg	16 [18]	16 [18]	16 [18]
Outdoor	Power Supply	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50
	Sound Pressure Level	dBA	46	49	52
	Height	mm	540	540	651
	Width	mm	700	700	855
	Depth	mm	250	250	328
	Net Weight	kg	28	30	47
	Pipe connection - Liquid	mm	6.35	6.35	6.35
	Pipe connection - Gas	mm	9.52	12.70	12.70
	Piping Length	m	12	12	12
Piping Elevation	m	5	5	8	

Indoor Model Name			FFQN25CXV1	FFQN35CXV1	FFQN50CXV1	FFQN50CXV1
Outdoor Model Name			RYN25CXV1	RYN35CXV1	RYN50CXV1	RYN50CXV1
Nominal Cooling Capacity	Btu/h	9500	12500	17500	18000	
	W	2780	3660	5129	5280	
Nominal Heating Capacity	Btu/h	9500	11500	17500	18500	
	W	2780	3370	5129	5420	
Nominal EER	W/W	3.09	2.82	3.03	3.06	
Nominal COP	W/W	3.35	3.30	3.00	3.63	
Indoor	Power Supply	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
	Air Flow	CFM	410/360/330	410/360/330	450/410/340	450/410/340
	Sound Pressure Level	dBA	41/38/35	41/38/34	44/41/37	44/41/37
	Height [with Panel]	mm	250 [295]	250 [295]	250 [295]	250 [295]
	Width [with Panel]	mm	570 [640]	570 [640]	570 [640]	570 [640]
	Depth [with Panel]	mm	570 [640]	570 [640]	570 [640]	570 [640]
	Net Weight [with Panel]	kg	16 [18]	16 [18]	16 [18]	16 [18]
Outdoor	Power Supply	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	380-415/3/50
	Sound Pressure Level	dBA	46	49	52	52
	Height	mm	540	540	651	651
	Width	mm	700	700	855	855
	Depth	mm	250	250	328	328
	Net Weight	kg	28	30	47	47
	Pipe connection - Liquid	mm	6.35	6.35	6.35	6.35
	Pipe connection - Gas	mm	9.52	12.70	12.70	12.70
	Piping Length	m	12	12	15	15
	Piping Elevation	m	5	5	8	8